






# Pressure Series 1830

Certified for:

Usage cycles  
200.000 cycles


Protects from:

-  Air
-  Water
-  Light
-  Insects




 Not an obstacle for disabled persons

## STANDARD ACCESSORIES





Standard measurements (mm)	430	530	630	730	830	930	1030	1130	1230	1330	1430	1530	1630	1730	1830	Longer lengths on request
Max shortening (mm)	120	100	100	100	100	100	100	100	100	100	150	150	150	150	150	

## FASTENING SYSTEMS




With side flaps (T)


 Mechanism (PATENTED) with the parallel descent of the moving profile with gasket, characterised by the DUAL ADJUSTMENT (screw E: descent - screw R: incline) for a strong even pressure on the entire length.

 **STANDARD:** Cardboard box with 32 pcs + 32 standard accessory packs.

## MAIN APPLICATIONS



Armoured door



 Extruded profiles in aluminium alloy 6060 - tubular extruded gasket in EPDM - elements printed in self-lubricating nylon + nylon reinforced with 30% glass fibre - threaded rods in burnished iron - 7mm hexagonal button and Ø 6 mm brass bushing - coil springs in treated stainless steel.

## OPTIONAL ACCESSORIES

Details on page 102

### 1 Nylon plate



CA104

 100 pcs pack  
 brown, white

### 2 Insulating nylon plate with silicon gasket


PI002


PI002-R

 20 pcs pack  
 brown, white

## Application examples

Smooth frame



 **BUTTON (E):** round nylon, square nylon, bevelled nylon, rolling nylon (pivot).  
**GASKET:** silicon tubular, brush.

 **OPTIONAL:** Cardboard box with 15 polyethylene bags with 1 pc + 1 standard accessory pack + assembly instructions.